
# **HOTSOAK 76**



## HOTSOAK SERIES MODEL # AI21AIR7242CHS



















### **SPECIFICATIONS:**

#### **GENERAL SPECIFICATIONS:**

Tub Size 71 1/4" x 41 1/2" x 24"

181 cm x 105 cm x 61 cm

Bathing Well 43 1/2" long

24 3/4" wide

21 1/4" interior depth

Shipping Weight Tub Weight Filled 188 lbs. / 85.5 kg 1359 lbs. / 618 kg 136 lbs. / 63 kg

Tub Weight Only 138 lbs. / 63 kg Gallons to Overflow 163 gal. / 618 L

#### **ELECTRICAL SPECIFICATIONS:**

Pump 1/15 HP; 1.3 AMP; 110V
Heater 1.5 kW; 12.5 AMP; 110V
Requirements 20 AMP; 110V, separate circuit required protected w/ Class A GFCI

#### **STANDARD EQUIPMENT:**

#### **Aquatic Quality Features:**

- 1.5 kW Inline Maintenance Heater
- Run-Dry Pump with 20-Minute Timer
- 2 Circulation Portal Covers
- Bath-Side On/Off Electronic Button
- "Quiet Pad" Anti-Vibration Pump Mount for Quiet Operation
- Slip Resistant Floor
- Extra Deep and Long Bathing Well
- Pre-leveled ABS Support Base
- Heat-bent Rigid PVC Piping for Optimum Sanitary Conditions
- Durable, Easy to Clean, Lucite® Cast Acrylic Surface
- Available in 8 Standard No-Charge Colors

#### UL & IAPMO Listed, Factory Tested Limited Lifetime Warranty

#### **OPTIONAL EQUIPMENT:**

- Chromatherapy LED Lighting\*
- Comfort Pillow Oval or Rectangle
- Bolt-On Grab Bars
  - White, Biscuit, Chrome, Polished Brass, Gold,
     Polished Nickel, Satin Nickel or Oil Rubbed Bronze
- Lift & Turn Waste and Overflow
  - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel or Oil Rubbed Bronze
- Cable Drive Waste and Overflow
  - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel, Oil Rubbed Bronze or Color Matched (Bone, White and Biscuit Only)
- Integral Tiling Flange (Customer must specify which
- side(s) should receive flange)
- Premium Colors

All acrylic colors featured by Aquatic match the industry's leading fixture manufacturers.

\*This whirlpool will need to be hard wired to the breaker box. Three outlets will be supplied on the whirlpool.

Fax-On-Demand Document #1251



The manufacturer accepts a 1/4" variance. There are variations on each tub and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building should be measured from the tub; Aquatic Industries, Inc. assumes no responsibility for preparatory work.

www.aquaticwhirlpools.com 800.555.5324